

PUB-NO: EP001020970A1

DOCUMENT-IDENTIFIER: 

TITLE: SWITCH GEAR

PUBN-DATE: July 19, 2000

INVENTOR-INFORMATION:

NAME	COUNTRY
TAKAHASHI, MASAYUKI	JP
SAKAI, MICHIO	JP
YORITA, MITSUMASA	JP
ITOTANI, TAKAYUKI	JP
MIYAMOTO, SEIICHI	JP
MARUYAMA, TOSHIMASA	JP
ITO, TAKEFUMI	JP
KAWAMATA, IWAO	JP
KIMURA, TOSHINORI	JP
KOYAMA, KENICHI	JP
SATO, SHINJI	JP
HISAMORI, YOUICHI	JP
SEKIYA, TAKASHI	JP

ASSIGNEE-INFORMATION:

NAME	COUNTRY
mitsubishi electric corp	JP

APPL-NO: EP98944259

APPL-DATE: September 28, 1998

PRIORITY-DATA: JP26461497A (September 29, 1997) , JP08233498A
(March 27, 1998)

INT-CL (IPC): H02B013/02 , H01H033/66

EUR-CL (EPC): H01H031/00 , H01H033/66 , H02B013/035

ABSTRACT:

CHG DATE=20000901 STATUS=O> A switchgear comprising: a bus conductor; a load conductor; a grounding conductor; a primary circuit switching portion for connecting and disconnecting the bus conductor and the load conductor, which includes a pair of a first fixed electrode and a first movable electrode; a ground switching portion for connecting and disconnecting the load conductor and the grounding conductor, which includes a pair of a second fixed electrode and a second movable electrode; a first drive device for driving the first movable electrode of the primary circuit switching portion; a second drive device for driving the second movable electrode of the ground switching portion; and a vacuum vessel; wherein one end of each of the bus conductor, the load conductor and the grounding conductor, the primary circuit switching portion and the ground switching portion are provided in the vacuum vessel, while the first drive device and the second drive device are provided outside the vacuum vessel. □